

Overview		
Dimensions	250 x 250 x 43.5 mm (9.8 x 9.8 x 1.7")	
WiFi Standard	WiFi 7	
Spatial Streams	10	
Coverage Area	185 m² (2,000 ft²)	
Max. Client Count	1000+	
Uplink	10 GbE 1 GbE	
Mounting	Ceiling, Wall, VESA (Pro Mount Included)	
Power Method	PoE++	
Performance		
MIMO		
6 GHz	4 x 4 (DL/UL MU-MIMO)	
5 GHz	4 x 4 (DL/UL MU-MIMO)	
2.4 GHz	2 x 2 (DL/UL MU-MIMO)	
Max. Data Rate		
6 GHz	11.5 Gbps (BW320)	
5 GHz	8.6 Gbps (BW240)	
2.4 GHz	688 Mbps (BW40)	
Antenna Gain		
6 GHz	6 dBi	
5 GHz	6 dBi	
2.4 GHz	5 dBi	
Max. TX Power		
6 GHz	24 dBm / 30 dBm	

5 GHz	30 dBm
2.4 GHz	23 dBm
Max. BSSIDs	8 per Radio
Supported Data Rates	
802.11be (WiFi 7)	7.3 Mbps to 11.4 Gbps (MCS0 - MCS13 NSS1/2/3/4, EHT 20/40/80/160/240/320)
802.11ax (WiFi 6)	7.3 Mbps to 4.8 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160)
802.11ac (WiFi 5)	6.5 Mbps to 3.4 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160)
802.11n	6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40)

Features

Wireless Meshing	✓
Band Steering	✓
802.11v BSS Transition Management	✓
802.11r Fast Roaming	✓
802.11k Radio Resource Management (RRM)	✓
Advanced Radio Management	✓
Real-Time Spectral Analysis	✓
Passpoint (Hotspot 2.0)	✓
Captive Hotspot Portal	
Custom Branding Landing Page	✓
Voucher Authentication	✓
Payment-Based Authentication	✓
External Portal Server Support	✓
Password Authentication	✓

Guest Network Isolation	✓
Private Pre-Shared Key (PPSK)	✓
WiFi Speed Limiting	✓
Client Device Isolation	✓
WiFi Schedules	✓
RADIUS over TLS (RadSec)	✓
Dynamic RADIUS-assigned VLAN	✓

Hardware

Max. Power Consumption	43W
Supported Voltage Range	42.5—57V DC
Networking Interface	(1) 10 GbE RJ45 port (1) 1 GbE RJ45 port
Weight	1.8 kg (4 lb)
Management	Ethernet
Enclosure Material	UV-stabilized polycarbonate, aluminum alloy
Mount Material	Stainless steel (SUS304), galvanized steel (SGCC)
LEDs	
System	R/G/B
Channel Bandwidth	HT 20/40, VHT 20/40/80/160, HE 20/40/80/160, EHT 20/40/80/160/240/320 (MHz)
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel
Operating Frequency	US/CA: 2400 - 2472 MHz U-NII-1: 5150 - 5250 MHz U-NII-2A: 5250 - 5350 MHz U-NII-2C: 5470 - 5725 MHz U-NII-3: 5725 - 5850 MHz U-NII-5 to U-NII-8 : 5925 - 7125 MHz Worldwide:

2400 - 2483.5 MHz
5150 - 5725 MHz
5925 - 7125 MHz

Ambient Operating Temperature	-30 to 50° C (-22 to 122° F)
Ambient Operating Humidity	5 to 95% noncondensing

Software

Application Requirements

UniFi Network	Version 9.2.87 and later
---------------	--------------------------

Mobile App	iOS™ version 10.24.1 and later Android™ version 10.25.2 and later
------------	--