

Multi-Mode Optical Modules



General Description

Model	BOM-MM-1G-300M	BOM-MM-2G-300M	BOM-MM-10G-300M	BOM-MM-25G-100M	BOM-MM-100G-100M
Form Factor	SFP	SFP	SFP+	SFP28	QSFP28

Transmission Specifications

Mode	Multi-Mode				
Data Rate	1.25G	2.5G	10G	25G	100G
Wavelength	850 nm				
Distance, Up to	300 m	300 m	300 m	100 m	100 m

Connector Specifications

Connector type	LC/UPC Duplex				MPO/MTP-12
----------------	---------------	--	--	--	------------

Mechanical Properties

Ambient Operating Temperature	0 to 70°C				
-------------------------------	-----------	--	--	--	--

Power

Max Consumption	1W	1W	1.5W	2W	3W
Hot-Pluggable	Yes				

Warranty

Term	3 Years				
------	---------	--	--	--	--

Compatibility

Designed for broad compatibility with networking equipment supporting the corresponding SFP, SFP+, SFP28, or QSFP28 interface. Compatible with MikroTik, Ubiquiti, Cisco, TP-Link, Zyxel, NETGEAR, Ruckus, ZTE, and D-Link networking equipment. Compatibility with other brands is available upon request.