

## Overview

Dimensions	379 x 355 x 105 mm (15 x 14 x 4.1")
Input Terminals	(32) Alarm sensor (1) Emergency
Power Method	PoE++/PoE+++ 12V SLA battery
Power Output Availability	PoE+++ input: 68W PoE++ input: 42W
NDAA Compliant	✓

## Mechanical

Weight	Device: 8.3 kg (18.3 lb) Mount: 624 g (1.4 lb)
Enclosure Material	SGCC steel housing with polycarbonate cover
Mount Material	SGCC steel
Mounting	Wall

## Hardware

Digital Input	(32) Inputs for alarm sensor (Compatible with EOL resistors: 1–5.6k $\Omega$ , 1k $\Omega$ included) (1) Emergency
Output Relay	(2) Wet/Dry Wet: 12V DC, 1A Dry: 30V DC, 1A
Aux Power Output	For sensor: (3) 12V DC, 1A right side total, (3) 12V DC, 1A left side total
Indoor and Outdoor Use	Indoor only

Ambient Operating Temperature	-10 to 40° C (14 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
Networking Interface	(1) 10/100 MbE RJ45 port
PoE Interface	(1) PoE++/PoE+++ input, 54V DC, 60W/90W (1) PoE+ output, 54V DC, 30W
Max. Power Consumption	90W
Battery Charge	SLA backup battery, 12V, 0.3A
LEDs	W/B <a href="#">Learn More</a>
Buttons	(1) Factory reset (2) Dry/Wet switch
Certifications	CE, FCC, IC

## Software

### Application Requirements

UniFi Protect	Version 7.0.88 and later
Mobile App	UniFi Protect iOS™ version 3.3.0 and later UniFi Protect Android™ version 3.2.0 and later